

On Searching a Table Consistent with Division Poset

Yongxi Cheng^{a,*}, Xi Chen^a, Yiqun Lisa Yin^b

^a Department of Computer Science, Tsinghua University, Beijing 100084, China

{cyx,xichen00}@mails.tsinghua.edu.cn

^b Independent security consultant, Greenwich CT, USA

yiqun@alum.mit.edu

Abstract

Suppose $P_n = \{1, 2, \dots, n\}$ is a partially ordered set with the partial order defined by divisibility, that is, for any two distinct elements $i, j \in P_n$ satisfying i divides j , $i <_{P_n} j$. A table $A_n = \{a_i | i = 1, 2, \dots, n\}$ of distinct real numbers is said to be *consistent* with P_n , provided for any two distinct elements $i, j \in \{1, 2, \dots, n\}$ satisfying i divides j , $a_i < a_j$. Given an real number x , we want to determine whether $x \in A_n$, by comparing x with as few entries of A_n as possible. In this paper we investigate the complexity $\tau(n)$, measured in the number of comparisons, of the above search problem. We present a $\frac{55n}{72} + O(\ln^2 n)$ search algorithm for A_n and prove a lower bound $(\frac{3}{4} + \frac{17}{2160})n + O(1)$ on $\tau(n)$ by using an adversary argument.

Keywords: Search algorithm; Complexity; Partially ordered set; Divisibility

1 Introduction

Suppose $P = \{1, 2, \dots, n\}$ is a partially ordered set (*poset*), we say a table $A = \{a_i | i = 1, 2, \dots, n\}$ of n distinct real numbers *consistent* with P , provided that for any $i, j \in P$ satisfying $i <_P j$, $a_i < a_j$. Given a table A of distinct real numbers which is consistent with a known poset P , and given a real number x , we want to determine whether $x \in A$, by making a series of comparisons between x and certain elements $a_i \in A$. The problem is considered in a model using pairwise comparisons of the form $x : a_i$ ($a_i \in A$) as basic operations. These comparisons have ternary outcomes $x < a_i$, $x = a_i$, or $x > a_i$. Our aim is to make as few comparisons as possible. The *complexity* of the problem is defined to be the minimum, over all search algorithms for P , of the maximum number of comparisons required in the worst case.

In this article we consider the above search problem for the case where the partial order is defined by divisibility. Let $P_n = \{1, 2, \dots, n\}$ be a poset with the partial order such that for any two distinct elements $i, j \in P_n$ satisfying i divides j , $i <_{P_n} j$. Thus we say a table $A_n = \{a_i | i = 1, 2, \dots, n\}$ of distinct real numbers consistent with P_n if for any two distinct elements $i, j \in \{1, 2, \dots, n\}$ satisfying i divides j , $a_i < a_j$. Denote by $\tau(n)$ the complexity of the problem searching a given real number x in A_n . We will investigate both upper bounds (i.e., search algorithms for A_n) and lower bounds on $\tau(n)$, our main result is the following

*Corresponding author.

Theorem 1.1 For $n \geq 1$, $c_1 n + O(1) \leq \tau(n) \leq c_2 n + O(\ln^2 n)$, where c_1 and c_2 are constants, and $c_1 = \frac{3}{4} + \frac{17}{2160} \approx 0.758$, $c_2 = \frac{55}{72} \approx 0.764$.

Throughout the paper, we denote by $\lceil x \rceil$ (ceiling of x) the least integer that is not less than x , denote by $\lfloor x \rfloor$ (floor of x) the largest integer that is not greater than x .

2 Related Work

In [5, 6] Linial and Saks studied the above class of search problems for general finite partially ordered set P . In [5] some general bounds on the complexity are provided, more precise results are also presented for the case that P is a product of chains and that P is a rooted forest. In [6] they proved that, for general finite partially ordered sets, the information theoretic bound for the complexity is tight up to a multiplicative constant.

There are different perspectives on the problem of searching posets. In [2], the authors studied the tradeoff between the preprocessing time and the subsequent search time in a partial order. Let $P(n)$ be the worst-case cost of a preprocessing algorithm which builds some partial orders, and let $S(n)$ be the maximum number of comparisons required to answer a membership query. They proved that $P(n) + n \log_2 S(n) \geq (1 + o(1))n \log_2 n$ for any comparison-based algorithm.

A different notion of searching a poset was studied in [1, 3]. They consider searching a given element x in a poset P , instead of searching a given real number in a table of real numbers consistent with P . In this case, for each comparison $x : p_i$ ($p_i \in P$) there are two possible outcomes: ‘yes’ indicates that x is ‘below’ p_i (less than or equal to p_i); ‘no’ indicates that x is not below p_i . The aim is to find the optimal search strategy. In spite of the similarity in definition, this turns out to be a quite different model. In [1], the authors gave a polynomial time algorithm for posets having tree structures. In [3], the authors proved that the problem is NP-hard in general, they also gave a $(1+o(1))$ -approximation algorithm under the *random graph* model and a 6.34-approximation algorithm under the *uniform* model, both of these run in polynomial time.

3 Easy Bounds on $\tau(n)$

First we give an easy lower bound $\frac{3n}{4}$ on $\tau(n)$ and a simple asymptotical cn algorithm searching A_n , where $c \approx 0.81$ is a constant.

3.1 Lower Bounds $(3/4)n$

It is easy to see that the following simple *response strategy* for the adversary can guarantee that at least $\frac{3n}{4}$ comparisons of the form $x : a_i$ ($a_i \in A_n$) are required to determine whether $x \in A_n$, for any search algorithm.

Response Strategy RS_1 : when the algorithm asks about $x : a_i$, $i = 1, 2, \dots, \lfloor \frac{n}{2} \rfloor$, answer $x > a_i$; when the algorithm asks about $x : a_i$, $i = \lfloor \frac{n}{2} \rfloor + 1, \dots, n$, answer $x < a_i$.

Focus on the subset $A_n^* = \{a_i \mid \frac{n}{4} < i \leq n\}$ of A_n , if the adversary answers queries in above way, the algorithm needs the comparison of x with each element $a_i \in A_n^*$ to determine whether $x = a_i$, thus needs at least $\frac{3n}{4}$ comparisons. In fact, the set $P_n^* = \{i \in P_n \mid \frac{n}{4} < i \leq n\}$ is a *section* (see [5]) of P_n , and there is no ordered chain having length more than two in P_n^* .

3.2 A Simple Search Algorithm

We will give an asymptotical cn algorithm searching A_n based on binary search, where $c = \sum_{t=0}^{\infty} \frac{1}{2^{2^t}} \approx 0.81$ is a constant. Define $B_i = \{a_j \in A_n | j = (2i - 1) \times 2^k (\leq n), k = 0, 1, \dots\}$, $i = 1, 2, \dots, \lceil n/2 \rceil$. Then $B_1, B_2, \dots, B_{\lceil n/2 \rceil}$ is a partition of A_n , and each B_i is in linear ordering. The algorithm runs as follows.

Algorithm 1 (*Searching Table A_n*): Binary search $B_1, B_2, \dots, B_{\lceil n/2 \rceil}$ one by one.

Now we analyze the number of comparisons required by Algorithm 1. For each B_i , binary search needs at most $\lceil \log_2(|B_i| + 1) \rceil$ comparisons, $i = 1, 2, \dots, \lceil n/2 \rceil$. Since $1 \leq |B_i| \leq \lfloor \log_2 n \rfloor + 1$, and the number of the sets B_i having exactly k elements is less than $n/2^{k+1} + 1$, it follows that the total number of comparisons required by Algorithm 1 is at most

$$\begin{aligned} s_1(n) &= \sum_{k=1}^{\lfloor \log_2 n \rfloor + 1} \left(\frac{n}{2^{k+1}} + 1 \right) \lceil \log_2(k + 1) \rceil \\ &< \sum_{k=1}^{\infty} \frac{n}{2^{k+1}} \lceil \log_2(k + 1) \rceil + \sum_{k=1}^{\lfloor \log_2 n \rfloor + 1} \lceil \log_2(k + 1) \rceil \\ &= n \cdot \sum_{t=0}^{\infty} \frac{1}{2^{2^t}} + O(\ln n \cdot \ln \ln n) \end{aligned}$$

4 Upper Bounds $\frac{55n}{72} + O(\ln^2 n)$ on $\tau(n)$

In this section we present a $\frac{55n}{72} + O(\ln^2 n)$ search algorithm for A_n , by partitioning A_n into 2-dimensional *layers* and then searching them one by one.

Let $I_n = \{i | 1 \leq i \leq n, i \text{ does not have factor 2 or 3}\}$. For each $i \in I_n$, extend a_i to a subset of A_n , L_i , such that $L_i = \{a_{i \times 2^k \times 3^s} \in A_n | k, s = 0, 1, 2, \dots\}$. For instance, for $n = 15$, we have subsets $L_1, L_5, L_7, L_{11}, L_{13}$, and

$$L_1 = \begin{bmatrix} a_1 & a_2 & a_4 & a_8 \\ a_3 & a_6 & a_{12} \\ a_9 \end{bmatrix} \quad L_5 = \begin{bmatrix} a_5 & a_{10} \\ a_{15} \end{bmatrix} \quad L_7 = [a_7 \quad a_{14}] \quad L_{11} = [a_{11}] \quad L_{13} = [a_{13}]$$

It is easy to see that all these subsets L_i (which sometimes will be referred to as *layers*), $i \in I_n$, form a partition of A_n .

An algorithm searching a real number x in an $m \times n$ ($m, n \geq 1$) *monotone matrix* (a matrix with entries increasing along each row and each column) was described in [5], which repeats comparing x with the element e at the top right corner of the current matrix, either the first row or the rightmost column of the current matrix will be eliminated depending on whether $x > e$ or $x < e$, thus the algorithm requires at most $m + n - 1$ comparisons (see [4, 5] for the lower bounds on the number of comparisons required for this problem when $m = n$). Based on this algorithm and notice that a layer is a “triangular” portion of a monotone matrix, we can apply the above “ $m + n - 1$ ” algorithm searching a layer. Furthermore, for some of the layers we can do slightly better by exploiting the properties of the layers.

Lemma 4.1 *If a layer L with $|L| \notin \{1, 2, 3, 5\}$, then one can search x in L using at most $m + n - 2$ comparisons, where m and n are the numbers of rows and columns of L , respectively.*

Proof. See Appendix A. ■

By Lemma 4.1 we can obtain an improved search algorithm for A_n .

Algorithm 2 (*Searching Table A_n*):

Search all layers L_i one by one. If $|L_i| \in \{1, 2, 3, 5\}$, search L_i using the “ $m + n - 1$ ” algorithm in [5]; Otherwise, search L_i using the “ $m + n - 2$ ” algorithm in Lemma 4.1.

Next we analyze the number of comparisons required by Algorithm 2. Define $r(L_i)$ and $c(L_i)$ to be the numbers of rows and columns of L_i respectively. The total number of comparisons required by Algorithm 2 is at most

$$\begin{aligned} s_2(n) &= \sum_{i \in I_n, |L_i| \in \{1, 2, 3, 5\}} (r(L_i) + c(L_i) - 1) + \sum_{i \in I_n, |L_i| \notin \{1, 2, 3, 5\}} (r(L_i) + c(L_i) - 2) \\ &= \sum_{i \in I_n} r(L_i) + \sum_{i \in I_n} c(L_i) - 2 \sum_{i \in I_n} 1 + \sum_{i \in I_n, |L_i| \in \{1, 2, 3, 5\}} 1 \end{aligned}$$

Clearly, $r(L_i) \leq 1 + \log_3 n$ for any $i \in I_n$. The number of layers L_i with $r(L_i) = p$ is less than $\frac{2n}{3^{p+1}} + 1$, since $3^{p-1}i \leq n$, $3^p i > n$ and i has no factor 2 or 3. Similarly, $c(L_i) \leq 1 + \log_2 n$ for any $i \in I_n$, and the number of layers L_i with $c(L_i) = q$ is less than $\frac{n}{3 \times 2^q} + 1$. It follows that

$$\begin{aligned} \sum_{i \in I_n} r(L_i) &< \sum_{p=1}^{1+\log_3 n} \left(\frac{2n}{3^{p+1}} + 1 \right) p < \sum_{p=1}^{\infty} \frac{2np}{3^{p+1}} + \sum_{p=1}^{1+\log_3 n} p = \frac{n}{2} + O(\ln^2 n), \\ \sum_{i \in I_n} c(L_i) &< \sum_{q=1}^{1+\log_2 n} \left(\frac{n}{3 \times 2^q} + 1 \right) q < \sum_{q=1}^{\infty} \frac{nq}{3 \times 2^q} + \sum_{q=1}^{1+\log_2 n} q = \frac{2n}{3} + O(\ln^2 n). \end{aligned}$$

In addition, $\sum_{i \in I_n} 1 = |I_n| = \frac{n}{3} + O(1)$, and

$$\sum_{i \in I_n, |L_i| \in \{1, 2, 3, 5\}} 1 = \sum_{i \in I_n, \frac{n}{2} < i \leq n} 1 + \sum_{i \in I_n, \frac{n}{3} < i \leq \frac{n}{2}} 1 + \sum_{i \in I_n, \frac{n}{4} < i \leq \frac{n}{3}} 1 + \sum_{i \in I_n, \frac{n}{8} < i \leq \frac{n}{4}} 1 = \frac{19n}{72} + O(1).$$

Therefore, $s_2(n) \leq \frac{55n}{72} + O(\ln^2 n)$.

5 Lower Bounds $(\frac{3}{4} + \frac{1}{432})n + O(1)$ on $\tau(n)$

In this section we prove a lower bound $(\frac{3}{4} + \frac{1}{432})n + O(1)$ on $\tau(n)$, by using an adversary argument. Thus the previous easy lower bound $\frac{3n}{4}$ is not best possible.

5.1 The Main Idea in Constructing Lower Bounds

Recall the response strategy RS_1 for the adversary given in Section 3, which guarantees that at least $\frac{3n}{4}$ comparisons are needed to determine whether $x \in A_n$ for any search algorithm. We can view RS_1 in the following way.

In Algorithm 2, A_n is partitioned into layers L_i . For each row R in each layer, if R has only one element, we pick this element and say that it forms a *unit*; if R has at least two elements, we pick the last two elements as a unit. We will call a unit consisting of one or two elements *1-unit* or *2-unit*, respectively. In total $\frac{3n}{4}$ elements are picked, which form exactly the subset $A_n^* = \{a_i | \frac{n}{4} < i \leq n\}$ of A_n . We can now restate response strategy RS_1 as follows.

response strategy for the elements in a 1-unit: For $\frac{n}{2} < i \leq n$, i is odd, when the algorithm asks about $x : a_i$, answer $x < a_i$.

$$\begin{bmatrix} \dots & \dots \\ \{ \lceil a_i \} \end{bmatrix}$$

response strategy for the elements in a 2-unit: For $\frac{n}{4} < i \leq \frac{n}{2}$, when the algorithm asks about $x : a_i$, answer $x > a_i$; when the algorithm asks about $x : a_{2i}$, answer $x < a_{2i}$.

$$\begin{bmatrix} \dots & \dots & \dots & \dots \\ \dots & \{ a_i \downarrow, \lceil a_{2i} \} \\ \dots & \dots \end{bmatrix}$$

response strategy for the elements do not belong to any unit: For $1 \leq i \leq \frac{n}{4}$, when the algorithm asks about $x : a_i$, answer $x > a_i$.

In general, if an algorithm compares x with a_i and gets the result $x < a_i$, then all the elements a_k with k divisible by i are known to be larger than x , thus could be eliminated from consideration, we say that these elements are *cut* by a_i . Similarly, if the algorithm gets the result $x > a_i$, then all the elements a_k with k that divides i are known to be smaller than x and could be eliminated, we also say that these elements are cut by a_i .

It is easy to see that under response strategy RS_1 , any element that belongs to some unit could not be cut by any other element. Therefore, if strategy RS_1 is adopted by the adversary, for any search algorithm in order to determine whether $x \in A_n$, the $\frac{3n}{4}$ comparisons of x with all the elements in all the units are necessary, thus obtaining the lower bound $\frac{3n}{4}$.

Hereafter, in some response strategy, the notation ' $a_i \downarrow$ ' means that when queried by any algorithm the comparison $x : a_i$, answer $x > a_i$, and we say that a_i *cuts to the left up*; ' $\lceil a_i$ ' means that when queried the comparison $x : a_i$, answer $x < a_i$, and we say that a_i *cuts to the right bottom*.

A natural thought for constructing better lower bounds could be: if more elements from each row are picked, can we prove that more than $\frac{3n}{4}$ comparisons are required? Picking three elements from a row makes no difference, since all elements in a row are in linear order, and two comparisons are sufficient for searching three ordered elements. Therefore, at least four elements should be chosen from some rows, to guarantee that at least three comparisons are required to search x in them.

We will pick elements in the following way. If there are less than four elements in a row, we pick all the elements as a unit; if there are at least four elements in a row, we pick the last four elements as a unit. However, in general, we could no longer guarantee, as we do under strategy RS_1 , that each of the elements picked can not be cut by other elements. Actually we even could not guarantee

that an element picked can not be cut by an element in other units. An element that can not be cut by any element outside its unit, under some response strategy, can guarantee the number of comparisons required by any search algorithm. We call this kind of elements *essential* (notice that an essential element may be cut by other elements in the same unit). Next we will present a more effective response strategy, in which there are sufficient essential elements to guarantee that more than $\frac{3n}{4}$ comparisons are required, for any search algorithm.

5.2 Units and Special Units

Let us start with some definitions. As described above, there is exactly one *unit* in each row of each layer. If in a row there are less than four elements, all these elements form a unit; if in a row there are at least four elements, the last four elements form a unit. A unit consisting of one, two, three, or four elements is called *1-unit*, *2-unit*, *3-unit*, or *4-unit* respectively. E.g., in the below layer (1), we have a 1-unit $\{a_{9i}\}$, a 3-unit $\{a_{3i}, a_{6i}, a_{12i}\}$, and a 4-unit $\{a_{2i}, a_{4i}, a_{8i}, a_{16i}\}$.

Next we introduce an important subcollection of the units defined above, called *special units*, which is the key to the proof of new lower bounds.

Definition 5.1 *special units*: A unit u is called a *special unit* if u is the 4-unit in a layer L_i with $|L_i| = 9$ (i.e., a layer L_i with $i \in S_n$, where $S_n = \{i | \frac{n}{18} < i \leq \frac{n}{16}, i \text{ is not divisible by } 2 \text{ or } 3\}$). We denote by 4-unit_s a special unit.

Since the form of a layer L_i is determined by its number of elements, $|L_i|$, a layer containing a special unit must have the following form (the marks ‘ $\lrcorner$ ’ and ‘ $\ulcorner$ ’ indicating the cut directions of the elements will be explained later in the new response strategy, RS_2). Each such layer contains exactly one special unit, $\{a_{2i}, a_{4i}, a_{8i}, a_{16i}\}$, in its first row.

$$\begin{bmatrix} a_i, & \{ a_{2i}\lrcorner, & \ulcorner a_{4i}\lrcorner, & \ulcorner a_{8i}\lrcorner, & \ulcorner a_{16i} \} \\ a_{3i}\lrcorner, & \ulcorner a_{6i}, & \ulcorner a_{12i} \\ \ulcorner a_{9i} \end{bmatrix} \quad (1)$$

A unit that is not a special unit is called a *general unit*, thus all 1-units, 2-units, and 3-units are general units, a subcollection of 4-units are general units.

Special units can help proving better lower bounds because we will prove later that, under response strategy RS_2 described below, all elements in special units are *essential*, thus each special unit guarantees at least three necessary comparisons for any search algorithm, which is one more than the two necessary comparisons guaranteed by the 2-unit in its row under RS_1 , consequently the lower bound $\frac{3n}{4}$ can be improved by the number of special units, $|S_n|$.

5.3 New Response Strategy

Now we are ready to describe the new response strategy for the adversary, and show that which can guarantee that at least $(\frac{3}{4} + \frac{1}{432})n + O(1)$ comparisons are required for any search algorithm to determine whether $x \in A_n$.

Response Strategy RS_2 :

for the elements not in a unit: For $1 \leq i \leq \frac{n}{16}$, when the algorithm asks about $x : a_i$, answer $x > a_i$.

for the elements in a 1-unit: For $\frac{n}{2} < i \leq n$, i is odd, when the algorithm asks about $x : a_i$, answer $x < a_i$.

$$\begin{bmatrix} \dots & \dots \\ \{ \lceil a_i \} \end{bmatrix} \quad (2)$$

for the elements in a 2-unit: For $\frac{n}{4} < i \leq \frac{n}{2}$, i is odd, when the algorithm asks about $x : a_i$, answer $x > a_i$; when the algorithm asks about $x : a_{2i}$, answer $x < a_{2i}$.

$$\begin{bmatrix} \dots & \dots & \dots \\ \{ a_i \lrcorner, \lceil a_{2i} \} \\ \dots \end{bmatrix} \quad (3)$$

The 3-units are partitioned into two classes according to the number of elements of the next row below them, which are denoted by 3-unit₁'s and 3-unit₂'s respectively.

for the elements in a 3-unit₁ (the 1st class of 3-units whose next row contains one element): For $\frac{n}{6} < i \leq \frac{n}{4}$, i is odd, when the algorithm asks about $x : a_i$, answer $x > a_i$; when the algorithm asks about $x : a_{2i}$ or $x : a_{4i}$, answer $x < a_{2i}$ or $x < a_{4i}$ respectively.

$$\begin{bmatrix} \dots & \dots & \dots & \dots \\ \{ a_i \lrcorner, \lceil a_{2i}, \lceil a_{4i} \} \\ \lceil a_{3i} \end{bmatrix} \quad (4)$$

for the elements in a 3-unit₂ (the 2nd class of 3-units whose next row contains two elements): For $\frac{n}{8} < i \leq \frac{n}{6}$, i is odd, when the algorithm asks about $x : a_i$ or $x : a_{2i}$, answer $x > a_i$ or $x > a_{2i}$ respectively; when the algorithm asks about $x : a_{4i}$, answer $x < a_{4i}$.

$$\begin{bmatrix} \dots & \dots & \dots & \dots \\ \{ a_i \lrcorner, a_{2i} \lrcorner, \lceil a_{4i} \} \\ a_{3i} \lrcorner, \lceil a_{6i} \end{bmatrix} \quad (5)$$

There are two classes of 4-units, general 4-units and special 4-units, which are denoted by 4-unit_g's and 4-unit_s's respectively.

for the elements in a 4-unit_g (general 4-unit): For $\frac{n}{16} < i \leq \frac{n}{8}$, $i \notin 2S_n$ (where $2S_n = \{2j | j \in S_n\}$, and see Definition 5.1 for S_n), when the algorithm asks about $x : a_i$ or $x : a_{2i}$, answer $x > a_i$ or $x > a_{2i}$ respectively; when the algorithm asks about $x : a_{4i}$ or $x : a_{8i}$, answer $x < a_{4i}$ or $x < a_{8i}$ respectively.

$$\begin{bmatrix} \dots & \dots & \dots & \dots & \dots & \dots \\ \dots & \{ a_i \lrcorner, a_{2i} \lrcorner, \lceil a_{4i}, \lceil a_{8i} \} \\ \dots & \dots & \dots & \dots \end{bmatrix} \quad (6)$$

for the elements in a 4-unit_s (special 4-unit): For $i \in S_n$, $\{a_{2i}, a_{4i}, a_{8i}, a_{16i}\}$ is a special unit. The response strategy for elements in a special unit is adaptive, depending on the order of comparisons with x made by the search algorithm, to guarantee that at least three comparisons are needed to determine whether $x \in \{a_{2i}, a_{4i}, a_{8i}, a_{16i}\}$.

- If the algorithm first asks about $x : a_{2i}$, answer $x > a_{2i}$. Then a_{2i} will be eliminated, and the remained three elements will follow the strategy $\{a_{4i} \lrcorner, \lceil a_{8i}, \lceil a_{16i}\}$ for possible subsequent comparisons with x .
- If the algorithm first asks about $x : a_{4i}$, answer $x > a_{4i}$. Then a_{2i} and a_{4i} are known to be smaller than x and will be eliminated, the remained two elements will follow the strategy $\{a_{8i} \lrcorner, \lceil a_{16i}\}$.
- If the algorithm first asks about $x : a_{8i}$, answer $x < a_{8i}$. Then a_{8i} and a_{16i} will be eliminated, and the remained two elements will follow the strategy $\{a_{2i} \lrcorner, \lceil a_{4i}\}$.
- If the algorithm first asks about $x : a_{16i}$, answer $x < a_{16i}$. Then a_{16i} will be eliminated, and the remained three elements will follow the strategy $\{a_{2i} \lrcorner, a_{4i} \lrcorner, \lceil a_{8i}\}$.

We denote the response strategy of elements in a special unit by $\{a_{2i} \lrcorner, \lceil a_{4i} \lrcorner, \lceil a_{8i} \lrcorner, \lceil a_{16i}\}$, see (1).

5.4 Lower Bounds $(\frac{3}{4} + \frac{1}{432})n + O(1)$ on $\tau(n)$

Recall that we call an element $a_i \in A_n$ *essential* under strategy RS_2 , if a_i belongs to some unit u (i.e., $i > \frac{n}{16}$), and any element not in u can not cut a_i under RS_2 .

Define set $E_n = \{\text{all elements of 1-units}\} \cup \{\text{all elements of 2-units}\} \cup \{\text{all the first and second elements of 3-unit}_1\text{'s}\} \cup \{\text{all the second and third elements of 3-unit}_2\text{'s}\} \cup \{\text{all the second and third elements of 4-unit}_g\text{'s}\} \cup \{\text{all elements of 4-unit}_s\text{'s}\}$. We can prove the following lemma.

Lemma 5.1 *Under response strategy RS_2 , all elements of E_n are essential.*

Proof of Lemma 5.1. See Appendix B. ■

By Lemma 5.1 and response strategy RS_2 , each essential element in general units needs one comparison with x to determine whether it equals x . For each special unit, at least three comparisons between x and its elements are needed to determine whether x is in it. By comparing the 1-units and 2-units picked for RS_1 in Section 5.1, we can see that under strategy RS_2 , each row containing a general unit contributes the same number of necessary comparisons as it contributes under RS_1 . While for each row containing a special unit, it contributes one more necessary comparison than it does under RS_1 . Therefore the lower bound $\frac{3n}{4}$ could be improved by the number of special units, $|S_n|$, which is $|\{i : \frac{n}{18} < i \leq \frac{n}{16}, i \text{ is not divisible by 2 or 3}\}| = (\frac{n}{16} - \frac{n}{18}) \times \frac{1}{3} + O(1) = \frac{n}{432} + O(1)$. Thus we get a new lower bound $(\frac{3}{4} + \frac{1}{432})n + O(1)$.

6 Improved Lower Bounds $(\frac{3}{4} + \frac{17}{2160})n + O(1)$ on $\tau(n)$

By recognizing more special units, we can extend the above method to obtain a better lower bound $(\frac{3}{4} + \frac{17}{2160})n + O(1)$ on $\tau(n)$. The units are defined in the same way as in Section 5.2, and we will introduce three classes of special units.

Definition 6.1 *the 1st class of special units (4-unit_{s,1}):* A unit u is of the 1st class of special units if u is the 4-unit in a layer L_i with $|L_i| = 9$ and i is not divisible by 5.

The definition of $4\text{-unit}_{s,1}$ is just Definition 5.1 of 4-unit_s with an extra restriction that i is not divisible by 5. A layer L_i containing a $4\text{-unit}_{s,1}$ must have the form (1), each such layer contains exactly one special unit $\{a_{2i}, a_{4i}, a_{8i}, a_{16i}\}$ in its first row. The subscripts $j = 2i$ of the first elements of all $4\text{-unit}_{s,1}$'s form a set $S_{n,1} = \{j(=2i) | \frac{n}{9} < j \leq \frac{n}{8}, j \text{ is divisible by 2, but is not divisible by 3, 4 or 5}\}$.

Definition 6.2 *the 2nd class of special units ($4\text{-unit}_{s,2}$):* A 4-unit u is of the 2nd class of special units if it has the following properties:

1. u is the 4-unit in the *first* row of a layer L_j with j not divisible by 5.
2. The first row of L_j has at least six elements and has two more elements than the second row of L_j .

The layers containing a $4\text{-unit}_{s,2}$ must have the following form (7), where the symbol ‘•’ indicates that there must exist an element at the position. Each such layer contains exactly one special unit, $\{a_i, a_{2i}, a_{4i}, a_{8i}\}$, in its first row. The subscripts i of the first elements of all $4\text{-unit}_{s,2}$'s form a set $S_{n,2} = \{i | \frac{n}{12} < i \leq \frac{n}{8}, i \text{ is divisible by 4, but is not divisible by 3 or 5}\}$.

$$\begin{bmatrix} \dots & \bullet & \bullet & \{a_i & \lceil a_{2i} \rceil & \lceil a_{4i} \rceil & \lceil a_{8i} \rceil\} \\ \dots & \bullet \lceil & \bullet \lceil & \lceil a_{3i} & \lceil a_{6i} \\ \dots & \dots & \dots & \dots \end{bmatrix} \quad (7)$$

Definition 6.3 *the 3rd class of special units ($4\text{-unit}_{s,3}$):* A 4-unit $u = \{a_i, a_{2i}, a_{4i}, a_{8i}\}$ is of the 3rd class of special units if it is in a layer L_j with j not divisible by 5, and has the following properties:

1. The subscript of its first element, i , is divisible by 36 (i.e., in L_j , there are at least two rows above u , and at least two columns before the first element a_i of u).
2. Denote by R the row containing u in L_j . The next row above R has two more elements than R , and the next row below R has two less elements than R .

A $4\text{-unit}_{s,3}$ in a layer must have the following form (8) (see Lemma C.1 in Appendix C), here we only list the subscripts.

$$\begin{bmatrix} \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots \\ \dots & \dots & \dots & \dots & \dots & \dots & \bullet & \bullet & \bullet & \bullet \\ \dots & \dots & \dots & \dots & \dots & \frac{4i}{3} \lceil & \frac{8i}{3} \lceil & \lceil \frac{16i}{3} & \lceil \frac{32i}{3} \\ \dots & \dots & \dots & \{i \lceil & \lceil 2i \lceil & \lceil 4i \lceil & \lceil 8i \lceil \\ \dots & \bullet \lceil & \bullet \lceil & \lceil 3i & \lceil 6i \\ \dots & \bullet & \bullet & \lceil 9i \\ \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots & \dots \end{bmatrix} \quad (8)$$

The subscripts i of the first elements of all $4\text{-unit}_{s,3}$'s form a set $S_{n,3} = \{i | \frac{n}{12} < i \leq \frac{3n}{32}, i \text{ is divisible by 4 and 9, but is not divisible by 5}\}$.

Based on the above new defined special units, we have the following response strategy.

Response Strategy RS_2^* : In RS_2^* , the response strategy for the elements in general units, in special units and not in any units are the same as their strategy in RS_2 respectively, with only a different partition of 4-units into general units and special units.

Similarly define set $E_n^* = \{\text{all elements of 1-units}\} \cup \{\text{all elements of 2-units}\} \cup \{\text{all the first and second elements of 3-unit}_1\text{'s}\} \cup \{\text{all the second and third elements of 3-unit}_2\text{'s}\} \cup \{\text{all the second and third elements of 4-unit}_g\text{'s}\} \cup \{\text{all elements of special units 4-unit}_{s,1}\text{'s, 4-unit}_{s,2}\text{'s and 4-unit}_{s,3}\text{'s}\}$. We can prove the following lemma.

Lemma 6.1 *Under RS_2^* , all elements of E_n^* are essential.*

Proof of Lemma 6.1. See Appendix C. ■

Using similar arguments as in Section 5.4, the lower bound $\frac{3n}{4}$ could be improved by the number of the new defined special units, $|S_{n,1}| + |S_{n,2}| + |S_{n,3}|$, which is

$$\begin{aligned} & \left(\frac{n}{8} - \frac{n}{9}\right) \times \frac{1}{4} \times \frac{2}{3} \times \frac{4}{5} + O(1) + \left(\frac{n}{8} - \frac{n}{12}\right) \times \frac{1}{4} \times \frac{2}{3} \times \frac{4}{5} + O(1) + \left(\frac{3n}{32} - \frac{n}{12}\right) \times \frac{1}{4} \times \frac{1}{9} \times \frac{4}{5} + O(1) \\ &= \frac{17n}{2160} + O(1). \end{aligned}$$

Therefore, we obtain an improved lower bound $(\frac{3}{4} + \frac{17}{2160})n + O(1)$.

7 Concluding Remarks and Open Problems

In this paper we investigate the complexity, $\tau(n)$, of the problem searching a table consistent with division poset. Our main result is the following. For $n \geq 1$, $c_1n + O(1) \leq \tau(n) \leq c_2n + O(\ln^2 n)$, where c_1 and c_2 are constants, and $c_1 = \frac{3}{4} + \frac{17}{2160} \approx 0.758$, $c_2 = \frac{55}{72} \approx 0.764$. It may be of interest to further close the gap.

Notice that under the model in this paper we only allow comparisons of the form $x : a_i$, i.e., all comparisons must involve x . If we also allow pairwise comparisons among elements of A_n , then the techniques used in this paper to prove lower bounds will not apply directly. It may be interesting to investigate the complexity of the search problem under this new model.

Acknowledgments

The authors are grateful to Andy Yao for introducing this interesting problem and insightful comments, to Xiaoming Sun and Chen Wang for helpful discussions.

References

- [1] Y. Ben-Asher, E. Farchi, and I. Newman, Optimal search in trees, *SIAM Journal on Computing*, 28 (6), 1999, 2090–2102.
- [2] A. Borodin, L. J. Guibas, N. A. Lynch, and A. C. Yao, Efficient searching using partial ordering, *Information Processing Letters*, 12 (2), 1981, 71–75.
- [3] R. Carmo, J. Donadelli, Y. Kohayakawa, and E. Laber, Searching in random partially ordered sets, *Theoretical Computer Science*, 321 (1), 2004, 41–57.
- [4] R. L. Graham and R. M. Karp, unpublished, Calif., 1968.
- [5] N. Linial and M. Saks, Searching Ordered Structures, *Journal of Algorithms*, 6, 1985, 86–103.
- [6] N. Linial and M. Saks, Every Poset Has a Central Element, *Journal of Combinatorial Theory, Series A*, 40, 1985, 195–210.

Appendices

A Proof of Lemma 4.1

It is easy to see that the form of L is determined by its cardinality $|L|$. First we prove two lemmas that will be useful later.

Lemma A.1 *In any layer, the difference of the lengths of any two consecutive rows must be 1 or 2.*

Proof of Lemma A.1. We prove the lemma by contradiction. Otherwise, at least one of the following two situations exists.

$$\left[\begin{array}{cc} \dots & a_i \\ \dots & a_{3i} \end{array} \right] \qquad \left[\begin{array}{cccccc} \dots & a_i & a_{2i} & a_{4i} & a_{8i} & \dots \\ \dots & a_{3i} & & & & \end{array} \right]$$

However, according to the definition of layers, the left one can not happen because the element a_{2i} should be in the layer, and the right one can not happen because the element a_{6i} should be in the layer. Thus the lemma holds. ■

Lemma A.2 *In any layer, there can not be three consecutive rows with lengths each increased by one.*

Proof of Lemma A.2. Otherwise, it must be the following situation.

$$\left[\begin{array}{cccc} \dots & a_i & a_{2i} & a_{4i} \\ \dots & a_{3i} & a_{6i} & \\ \dots & a_{9i} & & \end{array} \right]$$

However it can not happen since the element a_{8i} should be in the layer. The lemma holds. ■

Now we are ready to prove Lemma 4.1. By Lemma A.1, we have the following two cases.

Case 1. The first row of L has two more elements than the second row. Since $|L| \geq 4$, L must have the following form

$$\begin{bmatrix} \dots & a_i & a_{2i} & a_{4i} \\ \dots & a_{3i} & & \\ \dots & & & \end{bmatrix}$$

First compare x with a_{2i} .

If $x < a_{2i}$, then a_{2i} and a_{4i} are known to be greater than x , and will be eliminated from L , leaving a portion of an $m \times (n - 2)$ monotone matrix, which can be searched using at most $m + (n - 2) - 1$ comparisons. In total, at most $m + n - 2$ comparisons are needed.

If $x > a_{2i}$, then all elements in the first row except a_{4i} are known to be smaller than x , and will be eliminated. Then we compare x with a_{4i} and eliminate it, leaving a portion of an $(m - 1) \times (n - 2)$ monotone matrix, which can be searched using at most $(m - 1) + (n - 2) - 1$ comparisons. In total, at most $m + n - 2$ comparisons are needed.

Case 2. The first row of L has one more element than the second row. We can assume $|L| \geq 8$, since for $|L| = 4, 6$, or 7 it is easy to verify that the first row of L has two more elements than the second row, which belong to Case 1. When $|L| \geq 8$, by Lemma A.2 and A.1 the second row of L has two more elements than the third row, thus L must have the following form

$$\begin{bmatrix} \dots & a_i & a_{2i} & a_{4i} & a_{8i} \\ \dots & a_{3i} & a_{6i} & a_{12i} & \\ \dots & a_{9i} & & & \\ \dots & & & & \end{bmatrix}$$

First compare x with a_{4i} .

If $x < a_{4i}$ then the two rightmost columns are known to be greater than x and will be eliminated, leaving a portion of an $m \times (n - 2)$ monotone matrix, which can be searched using at most $m + (n - 2) - 1$ comparisons. In total, at most $m + n - 2$ comparisons are needed.

If $x > a_{4i}$ then all elements in the first row except a_{8i} are known to be smaller than x and will be eliminated. Then compare x with a_{8i} and eliminate it, leaving a portion of an $(m - 1) \times (n - 1)$ monotone matrix whose first row has two more elements than the second row. Thus it reduces to the situation of Case 1, which needs at most $(m - 1) + (n - 1) - 2$ comparisons. In total, at most $m + n - 2$ comparisons are needed.

Therefore, in either case $m + n - 2$ comparisons suffice.

B Proof of Lemma 5.1

We prove the lemma by contradiction. Suppose that, under RS_2 , $a_j \in E_n$ is not essential, i.e., there exists an element $a_i \in A_n$ that cuts a_j , and a_i is not in the unit containing a_j . We have the following two cases.

Case 1. a_i and a_j are in one layer. If a_i does not belong to any unit, then $i \leq n/16$ and a_i always cuts to the left up. If a_i cuts an element a_j , then $2j \leq i$, $32j \leq 16i \leq n$, which implying

that a_{2j} , a_{4j} , a_{8j} , a_{16j} all exist in the row containing a_j , thus a_j can not be in a unit. Therefore, a_i can not cut any element in a unit. If a_i belongs to a special unit, 4-unit_s , notice the form and the response strategy of special units, (1), it is easy to see that a_i can not cut any element $a_j \in E_n$ in a different unit in the same layer. If a_i belongs to a general unit, we have the following eight subcases.

1. a_i is the last element of a unit. Then a_i always cuts to the right bottom, $\{\dots, \lceil a_i \rceil\}$, and $2i > n$. If a_i cuts an element a_j , then $j \geq 2i > n$, which contradicts with $j \leq n$. Thus a_i can not cut any element.
2. a_i is the second last (first) element of a 2-unit, then it cuts to the left up, $\{a_i \lrcorner, a_{2i}\}$. If a_i cuts $a_j \in E_n$ in the same layer, then a_j must be the first element of a row above a_i . In addition, a_j must be in the next row R above a_i (since by Lemma A.2 the rows above R have at least 5 elements, if a_j is in a unit in those rows then a_j can not be the first element of that row). By Lemma A.1, R has 3 or 4 elements. If R has 3 elements, then it is a 3-unit_2 and its first element does not belong to E_n . If R has 4 elements, then it is a 4-unit_g and its first element does not belong to E_n .
3. a_i is the second last (second) element of a 3-unit_1 , then it cuts to the right bottom, $\{a_{i/2}, \lceil a_i, a_{2i} \rceil\}$. Notice the form of 3-unit_1 , (4), a_i can not cut any element in a different unit in the same layer.
4. a_i is the second last (second) element of a 3-unit_2 , then it cuts to the left up, $\{a_{i/2}, a_i \lrcorner, a_{2i}\}$. Since the row below a_i has two elements, by Lemma A.1 and Lemma A.2, the next row above a_i , R , has 5 elements. Thus, if a_i cuts $a_j \in E_n$ in the same layer, a_j must be in R , and is the first element of the 4-unit U of R . Notice the form of special units, (1), in which the bottom row has one element. Therefore, U is not a special unit and its first element does not belong to E_n .
5. a_i is the second last (third) element of a 4-unit_g , then it cuts to the right bottom, $\{a_{i/4}, a_{i/2}, \lceil a_i, a_{2i} \rceil\}$. Denote by U the 4-unit_g which a_i is in. Notice the form of general units, (6), a_j must be the last element of R , where R is the next row below a_i and has one less element than the row containing a_i . If R has at least four elements, then a_j must be the last element of a 4-unit_g , thus $a_j \notin E_n$. Otherwise R must have exactly three elements, then a_j must be the third element of R . Since R has one less element than the next row above it, by Lemma A.1 and Lemma A.2, the next row below R has one element, it follows that R is a 3-unit_1 , thus its third element $a_j \notin E_n$.
6. a_i is the third last (first) element of a 3-unit (3-unit_1 or 3-unit_2), then it cuts to the left up, $\{a_i \lrcorner, a_{2i}, a_{4i}\}$. If a_i cuts $a_j \in E_n$ in the same layer, a_j must be the first element of R , where R is the next row above a_i . In addition, R must contain exactly four elements. Notice the form of special units, (1), R is not a 4-unit_s , thus its first element $a_j \notin E_n$.
7. a_i is the third last (second) element of a 4-unit_g , then it cuts to the left up, $\{a_{i/2}, a_i \lrcorner, a_{2i}, a_{4i}\}$. In this case a_j must be in the next row above a_i , R . In addition, R has one more element than the row containing a_i , and a_j is the first element of the 4-unit U in R . Notice the form of special units, (1), U is not a 4-unit_s , thus its first element $a_j \notin E_n$.

8. a_i is the fourth last (first) element of a 4-unit_g, then it cuts to the left up, $\{a_{i \downarrow}, a_{2i}, a_{4i}, a_{8i}\}$. If a_i cuts an element a_j , then $2j \leq i$, $16j \leq 8i \leq n$, which implying that $a_{2j}, a_{4j}, a_{8j}, a_{16j}$ all exist in the row containing a_j , thus a_j can not be in a unit. Therefore, a_i can not cut any element in a unit.

Case 2. a_i and a_j are in different layers. We first prove the following lemma that will be useful later.

Lemma B.1 *For any $a_{j_1}, a_{j_2} \in A_n$ in different layers, if j_1 divides j_2 , then the quotient is at least 5.*

Proof of Lemma B.1. Suppose that $a_{j_1} \in L_{i_1}$ with $j_1 = i_1 \times 2^{k_1} \times 3^{s_1}$, $a_{j_2} \in L_{i_2}$ with $j_2 = i_2 \times 2^{k_2} \times 3^{s_2}$, where L_{i_1} and L_{i_2} are different layers (i.e., $i_1 \neq i_2$) and j_1 divides j_2 . Since i_1, i_2 have no factor 2 or 3, we have $k_1 \leq k_2$ and $s_1 \leq s_2$, and i_1 divides i_2 with quotient at least 5. It follows that j_1 divides j_2 with quotient at least 5. ■

There are seven subcases in Case 2.

1. a_i does not belong to any unit. Then $i \leq \frac{n}{16}$ and a_i always cuts to the left up, by using the same argument at the beginning of Case 1, a_i can not cut any element in a unit.
2. a_i is the last element of a unit. Then a_i always cuts to the right bottom, $\{\dots, \lceil a_i \rceil\}$, and $2i > n$. By using the same argument in subcase 1 of Case 1, a_i can not cut any element.
3. a_i is the second last element of a unit and cuts to the left up, $\{\dots, a_{i \downarrow}, a_{2i}\}$. By Lemma B.1, if a_i cuts $a_j \in E_n$ in a different layer then $5j \leq i$, $10j \leq 2i \leq n$, thus a_{2j}, a_{4j}, a_{8j} all exist in the row containing a_j . If $a_j \in E_n$, a_j can only be the first element of some special unit, it follows that $j/2 \in S_n = \{k \in I_n \mid \frac{n}{18} < k \leq \frac{n}{16}\}$ (see Definition 5.1), thus $9j > n$, which contradicts with $10j \leq n$.
4. a_i is the second last element of a unit and cuts to the right bottom, $\{\dots, \lceil a_i, a_{2i} \rceil\}$. Thus $4i > n$. By Lemma B.1, if a_i cuts $a_j \in E_n$ in a different layer, then $j \geq 5i > n$, which contradicts with $j \leq n$.
5. a_i is the third last element of a unit and cuts to the left up, $\{\dots, a_{i \downarrow}, a_{2i}, a_{4i}\}$. By Lemma B.1, if a_i cuts $a_j \in E_n$ in a different layer then $5j \leq i$, thus $20j \leq 4i \leq n$. It follows that $a_{2j}, a_{4j}, a_{8j}, a_{16j}$ all exist in the row containing a_j , thus a_j can not be in a unit, which contradicts with $a_j \in E_n$.
6. a_i is the third last element of a unit and cuts to the right bottom. In this case, a_i must be the second element of a special unit, $\{a_{i/2}, \lceil a_i, a_{2i}, a_{4i} \rceil\}$. It follows that $i/4 \in S_n = \{k \in I_n \mid \frac{n}{18} < k \leq \frac{n}{16}\}$, thus $i > \frac{2n}{9}$. However, by Lemma B.1, if a_i cuts $a_j \in E_n$ in a different layer then $j \geq 5i > \frac{9i}{2} > n$, which contradicts with $j \leq n$.
7. a_i is the fourth last element of a unit, i.e., the first element of a 4-unit, $\{a_{i \downarrow}, a_{2i}, a_{4i}, a_{8i}\}$. Then a_i always cuts to the left up, and by using the same argument in subcase 8 of Case 1, a_i can not cut any element in a unit.

C Proof of Lemma 6.1

We prove the lemma by contradiction. Suppose that, under RS_2^* , $a_j \in E_n^*$ is not essential, i.e., there exists an element $a_i \in A_n$ that cuts a_j , and a_i is not in the unit containing a_j . We have the following two cases.

Case 1. a_i and a_j are in one layer. If a_i does not belong to any unit, then a_i always cuts to the left up, by using the same argument at the beginning of Case 1 in the proof of Lemma 5.1, a_i can not cut any element in a unit. If a_i belongs to a special unit of the first or the second class, i.e., a $4\text{-unit}_{s,1}$ or $4\text{-unit}_{s,2}$, notice the forms of these special units, (1) and (7), it is easy to see that a_i can not cut any element $a_j \in E_n^*$ in a different unit in the same layer (for the case where a_i is in a $4\text{-unit}_{s,2}$, notice that the second row of any layer can not contain a special unit). For the case where a_i belongs to a special unit of the third class, i.e. a $4\text{-unit}_{s,3}$, we first give two lemmas that will be useful. Similarly as Lemma A.2, we have the following

Lemma C.1 *In any layer, there can not be four consecutive rows with lengths each increased by 2.*

The correctness of Lemma C.1 can be easily seen by noticing that in the third, fourth, fifth and sixth row in (8), $9i$ exists in the layer since $9i < \frac{32i}{3}$.

Lemma C.2 *If R is the next row above or below a $4\text{-unit}_{s,3}$ in the same layer, then R does not contain a special unit.*

Lemma C.2 is true since by the definition of $4\text{-unit}_{s,3}$, R is not the first row of its layer thus can not contain a $4\text{-unit}_{s,1}$ or a $4\text{-unit}_{s,2}$; and by Lemma C.1, R either has one less element than the next row above R or has one more element than the next row below R , thus can not contain a $4\text{-unit}_{s,3}$.

By Lemma C.2, if a_i belongs to a $4\text{-unit}_{s,3}$, a_i can not cut any element $a_j \in E_n^*$ in a different unit in the same layer.

If a_i belongs to a general unit, similarly as Case 1 in the proof of Lemma 5.1, we have the eight subcases. For all these subcases we can show that, using the same arguments in Lemma 5.1 correspondingly (sometimes when comes to special units, we only need to replace them with the new defined special units $4\text{-unit}_{s,1}$, $4\text{-unit}_{s,2}$ and $4\text{-unit}_{s,3}$), a_i can not cut $a_j \in E_n^*$.

Case 2. a_i and a_j are in different layers. We first give the following two lemmas that will be useful later.

Lemma C.3 *For any $a_{j_1}, a_{j_2} \in A_n$ in different layers, if j_1 divides j_2 , and j_2 is not divisible by 5, then the quotient is at least 7.*

Lemma C.4 *If i is the subscript of a first element in a special unit $4\text{-unit}_{s,1}$, $4\text{-unit}_{s,2}$ or $4\text{-unit}_{s,3}$, then $12i > n$.*

Lemma C.3 can be proved in a similar way as for Lemma B.1, and Lemma C.4 is true since by the definitions of $4\text{-unit}_{s,1}$'s, $4\text{-unit}_{s,2}$'s and $4\text{-unit}_{s,3}$'s, the row containing a special unit always has two more elements than the next row below it.

Similarly as Case 2 in the proof of Lemma 5.1, we have the following seven subcases. Except subcase 3 and subcase 6, we can apply the same arguments in Lemma 5.1 to all the following subcases correspondingly.

1. a_i does not belong to any unit. By using the same argument at the beginning of Case 1 in the proof of Lemma 5.1, a_i can not cut $a_j \in E_n^*$.
2. a_i is the last element of a unit. Then a_i always cuts to the right bottom, $\{\dots, \lceil a_i\}$. By using the same argument in subcase 1 of Case 1 in the proof of Lemma 5.1, a_i can not cut $a_j \in E_n^*$.
3. a_i is the second last element of a unit and cuts to the left up, $\{\dots, a_i \lrcorner, a_{2i}\}$. By Lemma B.1, if a_i cuts $a_j \in E_n^*$ in a different layer, we have $5j \leq i$, $10j \leq 2i \leq n$, thus a_{2j} , a_{4j} , a_{8j} all exist in the row containing a_j . If $a_j \in E_n^*$, a_j can only be the first element of a special unit. We have two possibilities about a_i .
 - (a) a_i is the first element of a 2-unit or the second element of a 3-unit₂. In this case a_j must be the first element of a 4-unit_{s,1}, since otherwise in the row containing a_j , there will be at least two elements before a_j , thus a_i can not cut a_j . However, by the form of 4-unit_{s,1}, (1), if a_j is the first element of a 4-unit_{s,1}, then $9j > n$, this contradicts with $10j \leq n$. Thus this possibility is eliminated.
 - (b) a_i is the third element of a special unit. By the definitions of the new defined special units, i is not divisible by 5. Thus by Lemma C.3, $7j \leq i$, $14j \leq 2i \leq n$. However, by Lemma C.4, if a_j is the first element of a special unit, then $12j > n$, which contradicts with $14j \leq n$.
4. a_i is the second last element of a unit and cuts to the right bottom, $\{\dots, \lceil a_i, a_{2i}\}$. By using the same argument in subcase 4 of Case 2 in the proof of Lemma 5.1, a_i can not cut $a_j \in E_n^*$.
5. a_i is the third last element of a unit and cuts to the left up, $\{\dots, a_i \lrcorner, a_{2i}, a_{4i}\}$. By using the same argument in subcase 5 of Case 2 in the proof of Lemma 5.1, a_i can not cut $a_j \in E_n^*$.
6. a_i is the third last element of a unit and cuts to the right bottom. In this case, a_i must be the second element of a special unit, $\{a_{i/2}, \lceil a_i, a_{2i}, a_{4i}\}$. By the form of 4-unit_{s,1}, (1), a_i can not be in a 4-unit_{s,1}, since otherwise we have $9 \times i/2 > n$, it follows that $j \geq 5i > n$. Therefore, a_i can only be the second element of a 4-unit_{s,2} or 4-unit_{s,3}, thus i is divisible by 8. By Lemma C.4, $12 \times i/2 > n$, thus $6i > n$, since $j \geq 5i$ it must be the case that $j = 5i$. Thus $2j = 10i > 6i > n$, a_j must be the last element of a unit. Since i is divisible by 8, $j = 5i$ is also divisible by 8, thus $a_{j/2}$, $a_{j/4}$, $a_{j/8}$ all exist in the row containing a_j , it follows that a_j is the last element of a 4-unit. Therefore, if $a_j \in E_n^*$, a_j must be the last element of a special unit. By the definitions of the new defined special units, j is not divisible by 5, which contradicts with $j = 5i$.
7. a_i is the fourth last element of a unit, i.e., the first element of a 4-unit, $\{a_i \lrcorner, a_{2i}, a_{4i}, a_{8i}\}$. By using the same argument in subcase 8 of Case 1 in the proof of Lemma 5.1, a_i can not cut $a_j \in E_n^*$.